



PII: S0735-1933(03)00012-5

TURBULENT MASS TRANSPORT IN SATURATED RIGID POROUS MEDIA

Marcelo J.S. de Lemos*

Maximilian S. Mesquita

Departamento de Energia - IEME

Instituto Tecnológico de Aeronáutica - ITA

12228-900 - São José dos Campos - SP - Brazil

*Corresponding Author. E-mail: delemos@mec.ita.br

(Communicated by J.P. Hartnett and W.J. Minkowycz)

ABSTRACT

This paper presents derivations of mass transport equations for turbulent flow in permeable structures. Equations are developed following two distinct procedures. The first method considers time averaging of the local instantaneous mass transport equation before the volume average operator is applied. The second methodology employs both averaging operators but in a reverse order. This work is intended to demonstrate that both approaches lead to equivalent equations when one takes into account both *time fluctuations* and *spatial deviations* of velocity and mass fraction. A modeled form for the final transport equation is presented where turbulent transfer is based on a macroscopic version of the k - ϵ model.

© 2003 Elsevier Science Ltd

Introduction

Modeling of macroscopic transport for incompressible flows in rigid porous media has been based on the volume-average methodology for either heat [1] or mass transfer [2-5]. If time fluctuations of the flow properties are considered, in addition to spatial deviations, there are two possible methodologies to follow in order to obtain macroscopic equations: *a*) application of time-average operator followed by volume-averaging [6-9], or *b*) use of volume-averaging before time-averaging is applied [10-13]. This work is intended to show that both sets of macroscopic mass transport equations are equivalent when examined under the recently established *double decomposition* concept [14-17]. This methodology, initially developed for the flow variables, has been extended to heat transfer in porous media where both time fluctuations and spatial deviations were considered for velocity and temperature [18]. A general classification of all proposed models for turbulent flow and heat transfer in porous media has been recently published [19]. Here, mass transport is considered.

Local Instantaneous Mass Transport Equation

The mass fraction distribution for the chemical species ℓ is governed by the following transport equation,

$$\frac{\partial \rho m_\ell}{\partial t} + \nabla \cdot (\rho \mathbf{u} m_\ell + \mathbf{J}_\ell) = \rho R_\ell \quad (1)$$

where m_ℓ is the mass fraction of component ℓ , defined as $m_\ell = \frac{\rho_\ell}{\rho}$, ρ_ℓ is the mass density of species ℓ (mass of ℓ over total volume) and ρ is the bulk density of the mixture ($\rho = \sum_\ell \rho_\ell$). Also, \mathbf{u} is the mass-averaged velocity of the mixture, $\mathbf{u} = \sum_\ell m_\ell \mathbf{u}_\ell$, where \mathbf{u}_ℓ is the velocity of species ℓ . Further, the mass diffusion flux \mathbf{J}_ℓ in (1) is due to the velocity slip of species ℓ ,

$$\mathbf{J}_\ell = \rho_\ell (\mathbf{u}_\ell - \mathbf{u}) = -\rho D_\ell \nabla m_\ell \quad (2)$$

where D_ℓ is the diffusion coefficient of species ℓ into the mixture. The second equality in equation (2) is known as Fick's Law. This constitutive equation is strictly valid for binary mixtures under the absence of any additional driving mechanisms for mass transfer [2]. The generation rate of species ℓ per unit of mixture mass is given in (1) by R_ℓ .

As mentioned, there are, in principle, two ways that one can follow in order to treat turbulent flow in porous media. The first method applies a time average operator to the governing equation (1) before the volume average procedure is conducted. In the second approach, the order of application of the two average operators is reversed. Both techniques aim at derivation of a suitable macroscopic turbulent mass transport equation.

Volume averaging in a porous medium, described in detail in references [20-22], makes use of the concept of a Representative Elementary Volume (REV), over which local equations are integrated. After integration, detailed information within the volume is lost and, instead, overall properties referring to a REV are considered. In a similar manner, statistical analysis of turbulent flow leads to time mean properties. Transport equations for statistical values are considered in lieu of instantaneous information on the flow.

Before undertaking the task of developing macroscopic equations, it is convenient to recall the definition of time average and volume average.

Volume and Time Average Operators- The Double Decomposition Concept

The volume average of φ taken over a Representative Elementary Volume in a porous medium can be written as:

$$\langle \varphi \rangle^v = \frac{1}{\Delta V} \int_{\Delta V} \varphi dV \quad (3)$$

The value $\langle \varphi \rangle^v$ is defined for any point \mathbf{x} surrounded by a Representative Elementary Volume, of size ΔV . This average is related to the *intrinsic* average for the fluid phase as:

$$\langle \varphi_f \rangle^v = \phi \langle \varphi_f \rangle^i \quad (4)$$

where $\phi = \Delta V_f / \Delta V$ is the medium porosity and ΔV_f is the volume occupied by the fluid in a REV.

Furthermore, one can write:

$$\varphi = \langle \varphi \rangle^i + {}^i\varphi \quad (5)$$

with $\langle {}^i\varphi \rangle^i = 0$. In equation (5), ${}^i\varphi$ is the *spatial deviation* of φ with respect to the intrinsic average $\langle \varphi \rangle^i$.

Further, the local volume average theorem can be expressed as [20-22]:

$$\begin{aligned} \langle \nabla \varphi \rangle^v &= \nabla (\phi \langle \varphi \rangle^i) + \frac{1}{\Delta V} \int_{A_i} \mathbf{n} \varphi dS \\ \langle \nabla \cdot \boldsymbol{\varphi} \rangle^v &= \nabla \cdot (\phi \langle \boldsymbol{\varphi} \rangle^i) + \frac{1}{\Delta V} \int_{A_i} \mathbf{n} \cdot \boldsymbol{\varphi} dS \\ \langle \frac{\partial \varphi}{\partial t} \rangle^v &= \frac{\partial}{\partial t} (\phi \langle \varphi \rangle^i) - \frac{1}{\Delta V} \int_{A_i} \mathbf{n} \cdot (\mathbf{u}_i \varphi) dS \end{aligned} \quad (6)$$

where \mathbf{n} is the unit vector normal to the fluid-solid interface and A_i is the fluid-solid interface area within the REV. It is important to emphasize that A_i should not be confused with the surface area surrounding volume ΔV .

Further, the time average of a general quantity φ is defined as:

$$\bar{\varphi} = \frac{1}{\Delta t} \int_t^{t+\Delta t} \varphi dt \quad (7)$$

where the time interval Δt is small compared to the fluctuations of the average value, $\bar{\varphi}$, but large enough to capture turbulent fluctuations of φ . Time decomposition can then be written as,

$$\varphi = \bar{\varphi} + \varphi' \quad (8)$$

with $\bar{\varphi}' = 0$. Here, φ' is the *time fluctuation* of φ around its average $\bar{\varphi}$.

Pedras and de Lemos [14,15] showed that for a rigid, homogeneous porous medium saturated with an incompressible fluid, the following relationships apply:

$$\begin{aligned} \overline{\langle \varphi \rangle^i} &= \langle \bar{\varphi} \rangle^i \\ \bar{\varphi} &= \overline{{}^i\varphi} \\ \langle \varphi' \rangle^i &= \langle \varphi \rangle^i \end{aligned} \quad (9)$$

Therefore, a general quantity φ can be expressed by either,

$$\varphi = \overline{\langle \varphi \rangle^i} + \langle \varphi \rangle^i + {}^i \overline{\varphi} + {}^i \varphi' \quad (10)$$

or

$$\varphi = \langle \overline{\varphi} \rangle^i + {}^i \overline{\varphi} + \langle \varphi' \rangle^i + {}^i \varphi' \quad (11)$$

Expressions (10) and (11) comprise the double decomposition concept where ${}^i \varphi'$ can be understood as either the *time fluctuation of the spatial deviation* or the *spatial deviation of the time fluctuation*. Also, $\langle {}^i \varphi' \rangle^i = \overline{{}^i \varphi'} = 0$.

Macroscopic Time Averaged Mass Transport Equations

To apply the volume average to (1), one has:

$$m_\ell = \langle m_\ell \rangle^i + {}^i m_\ell \quad (12)$$

$$\mathbf{u} = \langle \mathbf{u} \rangle^i + {}^i \mathbf{u} \quad (13)$$

Substituting (12) and (13) into (1), one obtains:

$$\frac{\partial \langle \langle m_\ell \rangle^i + {}^i m_\ell \rangle}{\partial t} + \nabla \cdot [\langle \langle \mathbf{u} \rangle^i + {}^i \mathbf{u} \rangle \langle \langle m_\ell \rangle^i + {}^i m_\ell \rangle] = \langle R_\ell \rangle^i + R_\ell + D_\ell \nabla^2 \langle \langle m_\ell \rangle^i + {}^i m_\ell \rangle \quad (14)$$

where the mixture density ρ and the coefficient D_ℓ in (2) have been assumed to be constant. Expanding the convection term and taking the volume average of (14) with the help of (6), one has:

$$\begin{aligned} \frac{\partial \phi \langle \langle m_\ell \rangle^i + {}^i m_\ell \rangle}{\partial t} + \nabla \cdot [\phi \langle \langle \langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i + {}^i \mathbf{u} \langle m_\ell \rangle^i + \langle \mathbf{u} \rangle^i {}^i m_\ell + {}^i \mathbf{u} {}^i m_\ell \rangle \rangle] = \\ \phi \langle \langle R_\ell \rangle^i + {}^i R_\ell \rangle + D_\ell \langle \nabla^2 \phi \langle \langle m_\ell \rangle^i + {}^i m_\ell \rangle \rangle \end{aligned} \quad (15)$$

or,

$$\frac{\partial \phi \langle m_\ell \rangle^i}{\partial t} + \nabla \cdot [\phi \langle \langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i + \langle {}^i \mathbf{u} \rangle^i \langle m_\ell \rangle^i \rangle] = \phi \langle R_\ell \rangle^i + D_\ell \nabla^2 (\phi \langle m_\ell \rangle^i) \quad (16)$$

The third term on the left of (16) appears in classical analysis of mass transport in porous media (e.g. [2-5]) and is known as **mass dispersion**.

In order to apply the time average to (16), one defines the intrinsic volume average as:

$$\langle m_\ell \rangle^i = \overline{\langle m_\ell \rangle^i} + \langle m_\ell \rangle^i \quad (17)$$

$$\langle \mathbf{u} \rangle^i = \overline{\langle \mathbf{u} \rangle^i} + \langle \mathbf{u} \rangle^i \quad (18)$$

Substituting (17) and (18) in (16) and taking the time average, we obtain:

$$\frac{\partial \phi \overline{\langle m_\ell \rangle^i}}{\partial t} + \nabla \cdot \phi \langle \overline{\langle \mathbf{u} \rangle^i} \overline{\langle m_\ell \rangle^i} + \overline{\langle \mathbf{u} \rangle^i} \overline{\langle m_\ell \rangle^i} + \overline{\langle {}^i \mathbf{u} \rangle^i} \overline{\langle m_\ell \rangle^i} \rangle = \phi \overline{\langle R_\ell \rangle^i} + D_\ell \nabla^2 (\phi \overline{\langle m_\ell \rangle^i}) \quad (19)$$

Equation (19) is the macroscopic mass transfer equation for the species ℓ in the porous matrix taking first the *volume average* followed by the *time average*.

Another route to reach a macroscopic transport equation for turbulent flow, it to invert the order of application of the same average operators applied over equation (1). Therefore, starting now with the time average, one needs to consider the time decompositions,

$$m_\ell = \bar{m}_\ell + m'_\ell \quad (20)$$

$$\mathbf{u} = \bar{\mathbf{u}} + \mathbf{u}' \quad (21)$$

Substituting (20) and (21) into (1) one has:

$$\frac{\partial(\bar{m}_\ell + m'_\ell)}{\partial t} + \nabla \cdot [(\bar{\mathbf{u}} + \mathbf{u}')(\bar{m}_\ell + m'_\ell)] = \bar{R}_\ell + R'_\ell + D_\ell \nabla^2(\bar{m}_\ell + m'_\ell) \quad (22)$$

where again the mixture density ρ and the diffusion coefficient D_ℓ were kept constants. Applying time average to (22) and one obtains,

$$\frac{\partial(\overline{\bar{m}_\ell + m'_\ell})}{\partial t} + \nabla \cdot (\overline{\bar{\mathbf{u}}\bar{m}_\ell + \bar{\mathbf{u}}'m'_\ell + \mathbf{u}'\bar{m}_\ell + \mathbf{u}'m'_\ell}) = \overline{\bar{R}_\ell + R'_\ell} + D_\ell \nabla^2(\overline{\bar{m}_\ell + m'_\ell}) \quad (23)$$

or

$$\frac{\partial \bar{m}_\ell}{\partial t} + \nabla \cdot (\overline{\bar{\mathbf{u}}\bar{m}_\ell} + \overline{\mathbf{u}'m'_\ell}) = \bar{R}_\ell + D_\ell \nabla^2 \bar{m}_\ell \quad (24)$$

The second term on the left of (24) is known as **turbulent mass flux** (divided by ρ). It requires a model for closure of the mathematical problem.

Further, in order to apply the volume average to (24), one must first define the spatial deviations with respect to the time averages, given by:

$$\bar{m}_\ell = \langle \bar{m}_\ell \rangle^i + {}^i \bar{m}_\ell \quad (25)$$

$$\bar{\mathbf{u}} = \langle \bar{\mathbf{u}} \rangle^i + {}^i \bar{\mathbf{u}} \quad (26)$$

Substituting now (25) and (26) into (24) and performing the volume average operation, one has:

$$\frac{\partial \phi \langle \bar{m}_\ell \rangle^i}{\partial t} + \nabla \cdot \phi (\langle \bar{\mathbf{u}} \rangle^i \langle \bar{m}_\ell \rangle^i + \langle {}^i \bar{\mathbf{u}} \bar{m}_\ell \rangle^i + \langle \bar{\mathbf{u}}' m'_\ell \rangle^i) = \phi \langle \bar{R}_\ell \rangle^i + D_\ell \nabla^2 \phi \langle \bar{m}_\ell \rangle^i \quad (27)$$

Equation (27) is the macroscopic mass diffusion equation for the taking first the *time average* followed by the *volume average* operator.

It is interesting to observe that (27), obtained through the first procedure (*time-volume average*), is equivalent to (19) as will be shown below.

Application of the Double Decomposition Concept

Using now (9)-(11), the fourth term on the left hand side of (19) can be expanded as:

$$\langle {}^i \mathbf{u} {}^i m'_\ell \rangle^i = \langle ({}^i \bar{\mathbf{u}} + {}^i \mathbf{u}') ({}^i \bar{m}_\ell + {}^i m'_\ell) \rangle^i = \langle {}^i \bar{\mathbf{u}} {}^i \bar{m}_\ell \rangle^i + \langle {}^i \mathbf{u}' {}^i m'_\ell \rangle^i \quad (28)$$

Substituting (28) into (19), the convection term will read,

$$\nabla \cdot \overline{(\phi \langle \mathbf{u} \ m_\ell \rangle^i)} = \nabla \cdot \{ \overline{\phi \langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i} + \overline{\langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i} + \overline{\langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i} + \overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} \} \tag{29}$$

↑
I

↑
II

↑
III

↑
IV

Likewise, applying again (9)-(11) to the fourth term on the left hand side of (27), one gets,

$$\overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} = \overline{\langle \langle \mathbf{u}' \rangle^i \langle m'_\ell \rangle^i + \langle \mathbf{u}' \rangle^i \langle m'_\ell \rangle^i \rangle} = \overline{\langle \mathbf{u}' \rangle^i \langle m'_\ell \rangle^i} + \overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} \tag{30}$$

Also, plugging (30) into (27) will give for the same convection term,

$$\nabla \cdot \overline{(\phi \langle \mathbf{u} \ m_\ell \rangle^i)} = \nabla \cdot \{ \overline{\phi \langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i} + \overline{\langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i} + \overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} + \overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} \} \tag{31}$$

↑
I

↑
II

↑
III

↑
IV

Comparing (31) to (29), in light of (9), one can conclude that (27) is, in fact, equal to (19). This demonstrates that the final expanded form of the macroscopic mass transfer equation for a rigid, homogeneous porous medium saturated with an incompressible fluid does not depend on the averaging order and both procedures lead to equivalent results.

Further, the four terms on the right of either (31) or (29) could be given the following physical significance (multiplied by ρ):

- I. **Convective Mass Flux** based on macroscopic time mean velocity and mass fraction.
- II. **Mass Dispersion** associated with deviations of microscopic time mean velocity and mass fraction. Note that this term is also present when analyzing laminar mass transfer in porous media, but it does not exist if a volume averaged in not performed.
- III. **Turbulent Mass Flux** due to the fluctuating components of both macroscopic velocity and mass fraction. This term is also present in turbulent flow in clear (non-porous) domains. It is not defined for laminar flow in porous media where time fluctuations do not exist.
- IV. **Turbulent Mass Dispersion** in a porous medium due to both *time fluctuations* and *spatial deviations* of both microscopic velocity and mass fraction.

Thus, the macroscopic mass transport equation for an incompressible flow in a rigid, homogeneous and saturated porous medium can be written as:

$$\frac{\partial \phi \langle \overline{m_\ell} \rangle^i}{\partial t} + \nabla \cdot \phi \langle \langle \mathbf{u} \rangle^i \langle \overline{m_\ell} \rangle^i + \langle \mathbf{u} \rangle^i \langle \overline{m_\ell} \rangle^i + \overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} + \overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} \rangle = \phi \langle \overline{R_\ell} \rangle^i + D_\ell \nabla^2 (\phi \langle \overline{m_\ell} \rangle^i) \tag{32}$$

or in its equivalent form (see (9)),

$$\frac{\partial \phi \langle m_\ell \rangle^i}{\partial t} + \nabla \cdot \phi \langle \langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i + \langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i + \overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} + \overline{\langle \mathbf{u}' \ m'_\ell \rangle^i} \rangle = \phi \langle R_\ell \rangle^i + D_\ell \nabla^2 (\phi \langle m_\ell \rangle^i) \tag{33}$$

Macroscopic Turbulence Model for Mass Transfer

All terms in (32) or (33) need to be represented or modeled as functions of the macroscopic mass fraction $\langle \bar{m}_\ell \rangle^i$. Using gradient type diffusion models, the proposed forms for the different mechanisms are as follows:

Mass Dispersion: Following the literature [2-5], a time-mean version for a dispersion model is given as,

$$\rho \langle \bar{\mathbf{u}}^i \bar{m}_\ell \rangle^i = \rho \mathbf{D}_{disp} \cdot \nabla \langle \bar{m}_\ell \rangle^i \quad (34)$$

where the dispersion coefficient \mathbf{D}_{disp} is a second order tensor.

Turbulent Mass Flux:

$$-\rho \overline{\langle \mathbf{u}'^i m'_\ell \rangle^i} = -\rho \overline{\langle \mathbf{u} \rangle^i \langle m_\ell \rangle^i} = \rho \mathbf{D}_t \cdot \nabla \langle \bar{m}_\ell \rangle^i \quad (35)$$

Turbulent Mass Dispersion:

$$-\rho \langle \bar{\mathbf{u}}^i m'_\ell \rangle^i = \rho \mathbf{D}_{disp,t} \cdot \nabla \langle \bar{m}_\ell \rangle^i \quad (36)$$

The coefficients \mathbf{D}_t and $\mathbf{D}_{disp,t}$ in equation (35) and (36), respectively, will be combined as suggested above by equation (30). Therefore, the two additional transport mechanisms, namely the *turbulent mass flux* and *turbulent mass dispersion*, can be added up so that a model for $\langle \bar{\mathbf{u}}^i m'_\ell \rangle^i$ will be necessary for closure of the mathematical problem.

Starting out from the time averaged mass transfer equation coupled with the microscopic modeling for the *turbulent mass flux vector* through the microscopic Eddy diffusivity, $D_{\ell,t} = \frac{\mu_t}{\rho Sc_{\ell,t}}$, one can write:

$$-\rho \overline{\langle \mathbf{u}'^i m'_\ell \rangle^i} = \rho D_{\ell,t} \nabla \bar{m}_\ell = \frac{\mu_t}{Sc_{\ell,t}} \nabla \bar{m}_\ell \quad (37)$$

where the microscopic Eddy Viscosity in (37), μ_t , is given by:

$$\mu_t = \rho c_\mu \frac{k^2}{\varepsilon} \quad (38)$$

and $Sc_{\ell,t}$ is the turbulent Schmidt number for the species ℓ , which is taken here as a constant. Also k and ε are the turbulent kinetic energy and its dissipation rate, respectively.

Applying the volume average to the resulting equation, one obtains the macroscopic turbulent mass flux vector, given by:

$$-\rho \langle \bar{\mathbf{u}}^i m'_\ell \rangle^i = \rho \langle D_{\ell,t} \rangle^i \nabla \langle \bar{m}_\ell \rangle^i = \rho (\mathbf{D}_t + \mathbf{D}_{disp,t}) \cdot \nabla \langle \bar{m}_\ell \rangle^i = \frac{\mu_t}{Sc_{\ell,t}} \nabla \langle \bar{m}_\ell \rangle^i \quad (39)$$

where the symbol μ_{t_ϕ} expresses the macroscopic version of the Eddy viscosity, given by:

$$\mu_{t_\phi} = \rho c_\mu \frac{\langle k \rangle^{i^2}}{\langle \varepsilon \rangle^i} \quad (40)$$

As mentioned above, in light of equations (30) and (39) the overall macroscopic mass flux due to turbulence is taken as the sum of the turbulent mass flux and the turbulent mass dispersion appearing in either (31) or (29). Further, the isotropic nature of expression (40) suggests the equality,

$$\mathbf{D}_t + \mathbf{D}_{disp,t} = \frac{1}{\rho} \frac{\mu_{t_\phi}}{Sc_{\ell,t}} \mathbf{I} \quad (41)$$

Likewise, a constant value for the molecular diffusion coefficient in (2) leads to a macroscopic diffusion coefficient, \mathbf{D}_{diff} , of the form,

$$\mathbf{D}_{diff} = \langle D_\ell \rangle^i \mathbf{I} = \frac{1}{\rho} \frac{\mu_\phi}{Sc_\ell} \mathbf{I} \quad (42)$$

Finally, using the Dupuit-Forchheimer relationship, $\mathbf{u}_D = \langle \bar{\mathbf{u}} \rangle^v = \phi \langle \bar{\mathbf{u}} \rangle^i$, in combination with (34), (42) and (41), the final modeled form for a transport equation can be written as,

$$\frac{\partial \phi \langle \bar{m}_\ell \rangle^i}{\partial t} + \nabla \cdot (\bar{\mathbf{u}}_D \langle \bar{m}_\ell \rangle^i) = \nabla \cdot \mathbf{D}_{eff} \cdot \nabla (\phi \langle \bar{m}_\ell \rangle^i) + \phi \langle \bar{R}_\ell \rangle^i$$

where

$$\mathbf{D}_{eff} = \mathbf{D}_{disp} + \mathbf{D}_{diff} + \mathbf{D}_t + \mathbf{D}_{disp,t} = \mathbf{D}_{disp} + \frac{1}{\rho} \left(\frac{\mu_\phi}{Sc_\ell} + \frac{\mu_{t_\phi}}{Sc_{\ell,t}} \right) \mathbf{I} = \mathbf{D}_{disp} + \frac{1}{\rho} \left(\frac{\mu_{\phi,ef}}{Sc_{\ell,ef}} \right) \mathbf{I} \quad (43)$$

In (42), $Sc_{\ell,ef}$ is the Effective Macroscopic Turbulent Schmidt number given by,

$$Sc_{\ell,ef} = \frac{\mu_{ef_\phi}}{\frac{\mu_\phi}{Sc_\ell} + \frac{\mu_{t_\phi}}{Sc_{\ell,t}}} \quad (44)$$

Conclusions

In this work it was shown that, under the light of the double decomposition concept [14, 15], both procedures employed to arrive at the macroscopic mass transfer equation, namely *time-volume averaging* or *volume-time averaging*, lead to the same result for the case of incompressible flow in a rigid, homogeneous porous medium. The extra terms appearing in equation still need to be modeled in terms of $\bar{\mathbf{u}}_D$ and $\langle \bar{m}_\ell \rangle^i$. It is expected that additional research on this new subject be stimulated by the derivations here presented.

Acknowledgements

The authors are thankful to CNPq, Brazil, for their financial support during the course of this research.

References

1. C. T. Hsu and P. Cheng, *Int. J. Heat Mass Transfer*, **33**, 1587 (1990).
2. J. Bear, *Dynamics of Fluids in Porous Media*, Dover, New York (1972).
3. J. Bear and Y. Bachmat, A generalized theory on hydrodynamic dispersion in porous media, *I.A.S.H. Symp. Artificial Recharge and Management of Aquifers*, Haifa, Israel, P.N. 72, pp. 7-16, I.A.S.H. (1967).
4. S. Whitaker, *Chem. Eng. Sci.*, **21**, 291 (1966).
5. S. Whitaker, *J. Amer. Inst. Chem. Eng.*, **3**(13), 420 (1967).
6. T. Maşuoka and Y. Takatsu, *Int. J. Heat Mass Transfer*, **39**(13), 2803 (1996).
7. F. Kuwahara, A. Nakayama and H. Koyama, *Journal of Heat Transfer*, **118**, 756 (1996).
8. F. Kuwahara and A. Nakayama, Numerical modeling of non-Darcy convective flow in a porous medium, *Heat Transfer 1998: Proc. 11th Int. Heat Transf. Conf.*, Kyongyu, Korea, vol. 4, pp. 411-416, Taylor & Francis Washington, D.C. (1998).
9. Nakayama and F. Kuwahara, *Journal of Fluids Engineering*, **121**, 427 (1999).
10. K. Lee and J.R. Howell, Forced convective and radiative transfer within a highly porous layer exposed to a turbulent external flow field, *Proceedings of the 1987 ASME-JSME Thermal Engineering Joint Conf.*, Honolulu, Hawaii, vol. 2, 377-386, ASME, New York, N.Y. (1987).
11. H. Wang and E.S. Takle, *Boundary Layer Meteorology*, **74**, 73 (1995).
12. B. V. Antohe and J. L. Lage, *Int. J. Heat Mass Transfer*, **40** (13), 3013 (1997).
13. D. Getachewa, W.J. Minkowycz and J.L. Lage, *Int. J. Heat Mass Transfer*, **43**, 2909 (2000).
14. M.H.J. Pedras and M.J.S. de Lemos, *Intern. Comm. Heat and Mass Transfer*, **27**(2), 211 (2000).
15. M.H.J. Pedras and M.J.S. de Lemos, *Intern. J. Heat and Mass Transfer*, **44**(6), 1081 (2001).
16. M.H.J. Pedras and M.J.S. de Lemos, *Numerical Heat Transfer - Part A Applications*, **39**(1), 35 (2001).
17. M.H.J. Pedras and M.J.S. de Lemos, *Journal of Fluids Engineering*, **123**(4), 941 (2001).
18. F.D. Rocamora Jr. and M.J.S. de Lemos, *Intern. Comm. Heat and Mass Transfer*, **27**(6), 825 (2000).
19. M.J.S. de Lemos and M.H.J. Pedras, *Journal of Fluids Engineering*, **123**(4), 935 (2001).
20. J.C. Slattery, *A.I.Ch.E. J.*, **13**, 1066 (1967).
21. S. Whitaker, *Indust. Eng. Chem.*, **61**, 14 (1969).
22. W. G. Gray and P. C. Y. Lee, *Int. J. Multiphase Flow*, **3**, 333 (1977).

Received September 19, 2002